



# NCR EasyPoint™ 62

## Specification

**MORE** ↗ **RESULTS**

Product dimensions	
<b>Height</b> With pedestal Without pedestal	1,438mm (56.6") 1,287mm (50.7")
<b>Width</b> With convenience shelves Without convenience shelves	825mm (32.5") 470mm (18.5")
<b>Depth</b> With convenience shelves Without convenience shelves With privacy wings Without privacy wings	755mm (29.7") 698mm (27.5") 755mm (29.7") 698mm (27.5")
<b>Weight</b> UL291 Level 1 construction safe Business hours safe	350kg (770lbs) 250kg (550lbs)
<b>Description</b>	Dedicated cash dispense ATM for interior locations

**Customer interface**

**Display**

307mm (12.1") SVGA standard colour LCD with autoscaling capability

8 tactile function display keys

**Keyboard**

Ruggedised tactile 16 key

Secure EPP (Encrypting PIN Pad): supports Triple DES and Remote Key Management

Certified as meeting the requirements of ISO

**Card reader**

DIP

Smart DIP: supports smart cards  
IMCRW (Integrated Motorised Card Reader Writer): option to support smart cards

CROPF (Card Return on Power Fail)

**Public & private audio**

Optional high quality sound or sound jack with volume control

**Media Entry & Exit Indicators (MEEI)**

For enhanced security and ease of use

**Camera**

Optional digital or third party camera

**Advertising panel**

**Colour customisation**

**Dispenser**

1 to 2 denominations

NCR multimedia cassette with 295mm (11.6") capacity

Spray presenter

**Printer**

**Receipt printer**

60mm graphics thermal printer

**Security**

Secure EPP: certified as meeting the requirements of ISO 9564-1, ISO 13491-1 and ISO 13491-2

Optional privacy wings

Optional enhanced PIN pad privacy

Smart DIP card reader: certified EMV 3.1.1 Level 1 and GIECB

IMCRW card reader: certified EMV 3.1.1 Level 1, EMV 4.0 Level 1, GIECB and ZKA

Optional pedestal anchor set

**Fraud countermeasures**

Options include: ECD (Enhanced Card Drive or 'Jitter'), illuminated MEEI in the card reader throat and ESS (Enhanced Shutter Security)

**Uninterruptible Power Supply (UPS)**

Optional integrated power management

**Safes**

UL291 Level 1 safe construction (business hours rated ATM)

UL291 business hours

**Accessibility**

**USA ADA Accessibility Guidelines for Buildings and Facilities (ADAAG)**

Subject to customer compliance with NCR Site Preparation and Installation Guidelines, the EasyPoint 62 complies with **ADAAG sections 4.34.2, 4.34.3 and 4.34.4** (as amended through September 2002). Of the remaining portions of ADAAG specifically addressed to automated teller machines, section 4.34.1 addresses the route on which the product is placed and not aspects of the product itself and section 4.34.5 is a performance standard that does not specify how to achieve or measure compliance and therefore NCR does not offer guidance as to such compliance.

**AS3769-1990 - Australian Standard for Accessibility**

With minor exceptions, the EasyPoint 62 produced for sale in Australia complies with this standard

**Access to ATMs: UK Design Guidelines 2002**

With minor exceptions, the EasyPoint 62 produced for sale in the UK conforms with these guidelines

**CAN/CSA B651.1-01**

With minor exceptions, the EasyPoint 62 produced for sale in Canada complies with this standard

**Additional features**

Electronic journal

**Options**

NCR intelligent power management

Pedestal

Convenience shelves

**Communication options**

TCP/IP

Leased line

Wireless communications enabled

Integrated ethernet

**Environmental**

Level 1 dust filtration

Optional Level 2 dust filtration

Optional Level 3 dust filtration

**Temperature**

10°C to 40°C (50°F to 104°F)

**Humidity**

20% to 80%

**Acoustics**

Sound power 65dBA idle, 68dBA operating

Sound pressure 65dBA operating

**Power requirements**

120V  
50Hz to 60Hz

220V to 240V  
50Hz to 60Hz

**Operating platform**

Intel® Celeron®

Intel® Pentium® III

Intel® Pentium® 4

CD ROM drive or DVD ROM drive

**Software**

Windows® XP

APTRA™ suite

APTRA enabled



Camera



DIP card reader



Encrypting PIN Pad



NCR Corporation, 1700 South Patterson Boulevard, Dayton, Ohio, 45479, USA

[www.ncr.com](http://www.ncr.com)

[www.self-service-touchpoints.com](http://www.self-service-touchpoints.com)

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

© 2004 NCR Corporation

All features, functions and operations described herein may not be marketed in all parts of the world. Consult your NCR representative for the latest information.

SP 3917